GARY R. HERBERT Governor SPENCER J. COX

Lieutenant Governor

State of Utah

DEPARTMENT OF NATURAL RESOURCES

MICHAEL R. STYLER Executive Director

Division of Oil, Gas and Mining JOHN R. BAZA Division Director

Minerals Inspection Report

Reviewed

Mine Name: Tom Taylor		Permit Number:	S/47/0065	Mine Status:	Reclaimed
Operator Name: Zeigler Chemical		Inspection Date:	5/5/2015	Permit Fees:	Paid
Inspector(s): A. Abate		Inspection Time:	11:00 AM	Bond Amount:	
Attendee(s): Stan Perks - BLM, Chip Zeigler, Zeigler		₩eather:	Clear 60F	Bond Escalation:	
Inspection Purpose: Determine if the site is in reclamation				Prior Inspection:	5/31/2007
OGN most	clusions and Recommendations It is not listed as a bond co-beneficiary on this permit. It is recommended that OGM retire the permit	to be met. For these reason	ame of the BLI ons, BLM shou	M only. Now that the recla	mation work is
Elements of Inspection			Evaluated & Commented	Enforcement	
1.	Permits, Revisions, Transfer, Bonds				П
	contract in 2007, but was never listed as a co-benefic directive on December 2, 2014 to reclaim the Tom Ta				
2.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The di	aylor mine by May 31, 20 mensions of the caps wer	15. The citati	on was terminated and the	fine was paid was on-site to
2.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls)	aylor mine by May 31, 20 imensions of the caps wer some discussion about ho	15. The citating re required to mow to make the	on was terminated and the	fine was paid was on-site to
2.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the capprotection of Drainages/Erosion Control	aylor mine by May 31, 20 imensions of the caps wer some discussion about ho	15. The citating re required to mow to make the	on was terminated and the in the landscaps blend with the landscaps.	fine was paid was on-site to
	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the confirmal projection of Drainages/Erosion Control Deleterious Material	imensions of the caps wer some discussion about he ap that was situated on a s	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the capprotection of Drainages/Erosion Control	imensions of the caps wer some discussion about he ap that was situated on a s	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the caprotection of Drainages/Erosion Control Deleterious Material Some concrete footings and metal cable were still on	imensions of the caps wer some discussion about he ap that was situated on a s	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3. 4.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the cap rotection of Drainages/Erosion Control Deleterious Material Some concrete footings and metal cable were still on were almost done.	imensions of the caps wer some discussion about he ap that was situated on a s	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3. 4.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the caprotection of Drainages/Erosion Control Deleterious Material Some concrete footings and metal cable were still on were almost done. Roads (maintenance, surfacing, dust control, safety)	imensions of the caps were some discussion about he ap that was situated on a s site. Mr. Zeigler indicate	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3. 4.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. Roads (maintenance, surfacing, dust control, safety) Reclamation	imensions of the caps were some discussion about he ap that was situated on a situate. Mr. Zeigler indicate including, hoist house an	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3. 4. 5. 6.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the confirm that the caps met their standards. There was prevent water from eroding around the edges of the confirm that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards. There was prevent water from eroding around the edges of the confirming that the caps met their standards around the edges of the confirming that the caps met their standards around the edges of the confirming that the caps met their standards around the edges of the confirming that the caps met their standards around the edges of the confirming that the caps met their standards around the edges of the confirming that the caps met their standards around the edges of the confirming that the caps met their standards around the edges of the confirming the caps around the edges of the confirming that the caps are caps around the edges of the confirming that the caps are caps around the edges of the confirming that the caps are caps around the caps a	imensions of the caps were some discussion about he ap that was situated on a situate. Mr. Zeigler indicate including, hoist house an	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3. 4. 5. 6.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the caprotection of Drainages/Erosion Control Deleterious Material Some concrete footings and metal cable were still on were almost done. Roads (maintenance, surfacing, dust control, safety) Reclamation All major structures have been removed from the site Backfilling/Grading (trenches, pits, roads, highwalls,	imensions of the caps were some discussion about he ap that was situated on a situate. Mr. Zeigler indicate including, hoist house an	re required to now to make the steep hillside.	neet BLM standards. BLM caps blend with the landsc	was on-site to ape and to
3. 4. 5. 6. 7. 8.	directive on December 2, 2014 to reclaim the Tom Ta on February 24, 2015. Public Safety (shafts, adits, trash, signs, highwalls) A total of 5 shafts were capped with concrete. The diconfirm that the caps met their standards. There was prevent water from eroding around the edges of the confirm that the caps met their standards. There was prevent water from eroding around the edges of the confirm that the caps met their standards. There was prevent water from eroding around the edges of the confirm that the caps met their standards. There was prevent water from eroding around the edges of the confirm that the caps met their standards. There was prevent water from eroding around the edges of the confirmation and metal cable were still on were almost done. Roads (maintenance, surfacing, dust control, safety) Reclamation All major structures have been removed from the site Backfilling/Grading (trenches, pits, roads, highwalls, Soils	imensions of the caps were some discussion about he ap that was situated on a situate. Mr. Zeigler indicate including, hoist house an shafts)	re required to mow to make the steep hillside.	neet BLM standards. BLM caps blend with the landscaps blend with the landscaps amation work is still progre	fine was paid was on-site to ape and to ssing and they ved on the site.

CC: Stan Perks, BLM

Chip Zeigler, Zeigler Chemical Company chip@zeiglerchemical.com

 $File: \ / nrwogmfs 1/OGM/GROUPS/MINERALS/WP/M047-Uintah/S0470065-TomTaylor/inspections/Insp-06032015.pdf$



Mine: S/47/0065 Inspected: 5/5/2015



The concrete cap is located just below the juniper trees. Some concrete was still present at the time of the inspection. The operator was in the process of removing it.



The BLM inspects the concrete caps to make sure they meet their requirements.



View of one of the five the concrete caps located on a steep slope.



Small rubble piles were still on-site at the time of the inspection that the operator was in the process of cleaning up.

